



Insulated Flexible Ducts



AT-Flex- 016

AT-Flex Insulated Flexible Duct is made to comply to UL-USA and ISO standard, Conforming to EU Standards with tough Metalised Polyester material; inner core is permanently bonded with fire retardant adhesive to a spring steel wire helix and manufactured for maximum thermal value. Additionally, thermal efficiency is provided by wrapping the exterior with a high tech 16 Kg Fiberglass insulation blanket. The state of the art outer jacket/ vapor barrier is made of durable quality Polyester.

Performance Data

Velocity: 5,000 fpm maximum

Fire Rating: Guaranteed to meet or exceed UL-USA, British Standard-UK and AS-Australia standards

Puncture test: Same as UL 181 – USA, Part 14

Temperature Range: 32 – 240 degrees F

Pressure: 8" – 10" Maximum Working Pressure

Insulation R Value: 4.2

Fiber Glass Insulation: 25 mm, 16 Kg/M3 High Density

Size: All Diameters available 4" to 18", Standard length 25ft or 7.6 M

Packing: 1 pc per box

شركة ادفانس تكنولوجيكال لقطع الغيار (ش.م.م.)

ADVANCE TECHNICAL PARTS CO. (L.L.C.)

REFRIGERATION, AIR CONDITIONING, ELECTRICAL PARTS & EQUIPMENT

DUBAI, U.A.E.

P. O. BOX 55784

TEL. : 2278100 / 2242002

FAX : 2277997

ABU DHABI, U.A.E.

P. O. BOX 28313

TEL. : 6 2 1 1 3 1 1

FAX : 6 2 1 1 3 1 0

E-MAIL : advance@emirates.net.ae